

WATER LEVELS PACKERS



WATER LEVELS

APAGEO proposes water level with acoustic signal and led, flat or round cable.

Length	30 m	50 m	100 m	150 m	200 m
Round cable	M4 04003001	M4 04005001	M4 04010001	M4 04015001	M4 04020001
Flat cable	M4 04003002	M4 04005002	M4 04010002	M4 04015002	M4 04020002

BOREHOLES AND WELLS CAMERA

APAGEO proposes boreholes and wells camera with a maximum length of 500 meters. The complete system consist of: reel and camera head, display unit with integrated LCD, USB2 grabber board and microphone, battery charger. Pictures, movies and comments can be saved to any external laptop. The equipment is easy to use, reliable, a compact and light weight instrument for field operations.



PACKERS

Low pressure packer, single or double, for injection with piston pump ¹ or permeability test (Lugeon test ²). Diameters 42 to 72 mm. Max. inflation pressure = 40 bar. Diameter 85 to 170 mm also available, please contact us.

¹ see p.25 ² see p.41

Ø (mm)	Ø Max (mm)	NPT	Single packer sleeve length		Double packer sleeve length	
			0,5 m	1,0 m	0,5 m	1,0 m
42	80	1/2"	B1 9105314	B1 9105315	B1 9105318	B1 9105319
54	130	1"	B1 9105308	B1 9105309	B1 9105300B1 9105301	
72	160	1 1/4"	B1 9105310	B1 9105311	B1 9105304	B1 9105305

HIGH PRESSURE SINGLE PACKER

Diameters 30 and 42 mm. Max. inflation pressure = 100 bar

Ø (mm)	Ø Max (mm)	NPT	Sleeve length	
			0,3 m	0,4 m
30	55	3/8 G	B2 0000200	-
42	85	3/4 G	-	B2 0000001

ACCESSORIES FOR PACKER

Reference

Hand pump for water inflation
- Capacity 60 bar
- With manometer + tank

B1 9400001



Pilot valve nitrogen inflation
- To be used with the Pressuremeter regulator [see p.67](#)

A1 1902215

