

DRAG BITS

APAGEO OFFERS AMERICAN DRAG BITS, CHEVRON TYPE FOR MEDIUM SOFT FORMATIONS, OR STEP TYPE FOR SOFTER FORMATIONS. THESE TOOLS OFFER OPTIMAL QUALITY.



Diameter		THREAD
Ø Inch	Ø mm	
2"3/8	60.32	A Rod or N Rod
2"1/2	63.50	
2"5/8	66.67	
3"	76.20	
3"1/4	82.55	
3"1/2	88.90	
3"1/2	88.90	
3"3/4	95.20	
3"7/8	98.43	
4"	101.6	
4"1/4	107.95	2"3/8
4"3/8	111.13	
4"1/2	114.30	
4"3/4	120.65	
4"7/8	123.83	
5"	127.00	
5"1/8	130.18	
5"1/4	133.35	
5"3/8	136.53	
5"1/2	139.70	

Available in hexagonal connection for auger drilling

Diameter		THREAD
Ø Inch	Ø mm	
5"5/8	142.88	2"3/8 or 3"1/2
5"3/4	146.05	
5"7/8	149.23	
6"	152.40	
6"1/8	155.58	
6"1/4	158.75	
6"1/2	165.10	
6"3/4	171.45	
7"	177.80	
7"1/8	180.97	
7"3/8	187.33	3"1/2
7"1/2	190.5	
7"5/8	193.68	
7"7/8	200.03	
8"	203.20	
8"1/8	206.38	
8"1/2	215.90	
8"3/4	222.25	
10"	254	
10"5/8	269.9	
12"1/4	311.1	3"1/12 or 4"1/2
13"3/4	349.2	
14"	355.6	
14"3/4	374.6	
17"1/2	444.5	
20"	508	
24"	603.6	
		6"5/8